



MAINTENANCE

26 Point Inspection Checklist

Use the 26 Point Inspection Checklist to explain required service for the *Evinrude E-TEC* 300 hour/3 year service, and to help “sell” a maintenance plan to your customer. The parts department can use the checklist to stock service supplies. Service technicians can use the checklist to check off service items as they are completed.

Description	Engine Care Product	Every 300 hours or 3 years ⁽¹⁾
Emergency stop circuit and lanyard (check operation)		X
Controls, steering and tilting, check operation		X
Engine mounting hardware, re-tighten		X
Fasteners, tighten any loosened components		X
Water intake screens, check condition		X
Cooling system, check water pump indicator		X
Anticorrosion anodes, check condition		X
Gearcase, check condition		X
Propeller, check condition		X
Fuel and oil systems, inspect and repair leaks		X
Check battery connections and condition		X
Access <i>EMM</i> information (resolve any service codes)		X
Electrical and ignition wires (inspect for wear or chafing)		X

Description	Engine Care Product	Every 300 hours or 3 years ⁽¹⁾
Fuel filter, replace ⁽²⁾		X
Gearcase lubricant, replace	A	X
Spark plugs, inspect or replace ⁽³⁾		X
Thermostats, inspect and check operation ⁽³⁾		X
Grease fittings, lubricate	C	X
Power trim/tilt and fluid level, inspect	B	X
Propeller shaft splines, inspect and lubricate ⁽⁴⁾	C	X
Starter pinion shaft, inspect and lubricate ⁽⁴⁾	D	X
Control cables, inspect and adjust		X
Steering cable, inspect and lubricate		X
Water pump, inspect / replace		X
Exhaust back pressure fitting (if equipped)		X
Oil filters remote tank / engine (115 – 300 HP models)		X

(1) Average recreational use. Commercial use, heavy use or use in salt or polluted water requires more frequent inspection and maintenance.

(2) Boat mounted fuel water separating filters should be replaced annually

(3) Emission-related component.

(4) Annually in salt water applications

A – *HPF Pro* Gearcase Lubricant

B – Trim and Tilt Fluid, use Biodegradable Fluid on single ram hydraulic systems, use Power Trim and Tilt Fluid on three ram hydraulic systems

C – *Triple Guard* Grease

D – Use Starter Bendix Lube only